

10-03-2012

Pos.	Art.No.	Qty.	Description	Price USD
------	---------	------	-------------	--------------

Thank you for your interest in ENGEL machines.
We are pleased to offer the following quotation.

01	d003527350		ENGEL INJECTION MOULDING MACHINE duo 11050/1000 WP US	
02	d010501000		Engel North America molding machine package: - Nozzle body with interchangeable tip, 3/4" radius and 1/4" orifice. Nozzlebody-to-tip thread is 7/8"-14UNF-2B. Barrelhead-to-nozzle body thread 1 3/4"-8UN-2A - Mechanical safety device for closing - 480V/3P/60cy incoming voltage and 480V barrel heat with 120V nozzle heat - Electrical equipment for USA and Canada - ANSI B151.1 compliant - Solid purge guard cover, with PC-window - SPI mold mounting and ejector pattern - Hydraulic ejector (platen ejector as option from 2200 US to), ejector holes are counter bored through holes for 3/4" screws. - Emergency stop function bE10, not to open safety gate behind moving plate (bE10) - Tool kit containing allen and open end wrenches	

Injection unit:

Short design with 2 hydraulic-cylinders for injection, direct drive of screw
Specific injection pressure switchover
Barrel removal to the top
Ceramic heaterbands
For processing of thermoplastics
regulated traverse cooling

Pos.	Art.No.	Qty.	Description	Price USD
			Melt barrel and screw, diameter 120 mm Barrel in bi-metallic-execution M3, higher abrasion- and corrosion resistant, working range up to 350 degrees C	
03	d050505355		barrel L/D 25 - 120 mm incl. 1 additional barrel heating	
04	d050513701		Barrier-screw S13 with B-mixing head L/D 25 - diameter 120 mm incl. check valve R9b	
05	d050541400		add. price for corrosion resistant barrelhead	
06	d050543549		Pneumatic shut off nozzle Nozzle tip thread 7/8"-14 UNF Nozzle radius 3/4" Nozzle orifice 1/4" OPT125222	
07	d059045400		insulating pads for heaterbands	
08	d059045900		Hopper support, moveable (hopper not included in shipment)	
09	d059046100		magnetic grid	
10	d059046700		speed controlled electrical screw drive nominal motor value 107 kW torque 10000 Nm 60 % by working of operating time from cycle Hint: for FI fused voltage network the main supply situation has to be discussed with the customer.	
11	d059046800		additional price for electrical screw drive in US-execution	
12	d059070150		Maintainance and service platform (fixed ladder with platform) for manual filling of the hopper according EN ISO 14122 1-4 and EN 201/20xx.	

Pos.	Art.No.	Qty.	Description	Price USD
------	---------	------	-------------	--------------

(ES 7050/. - ES 11050/.)

Clamp unit:

Fully hydromech. clamp unit in 2-platen exec.
 4 short stroke pressure pads on nozzle side
 4 adjustment nuts on ejector side
 2 fast movement cylinders placed diag.
 Hydraulic platen ejector,
 Platen stroke dependent on mold height.
 Moveable platen guided on base.
 Clamp force: 9000 kN (1000 US Tons)
 Technical data and standard equipment
 according to data sheet

13	d100043020	corepull single on movable platen (Euromap 13 / AN-147)
14	d100043025	corepull additional on movable platen
15	d100043030	corepull single on fixed platen (Euromap 13 / AN-147)
16	d100043046	pressure release for all corepulls on movable platen
17	d100043047	pressure release for all corepulls on fixed platen
18	d100043082	enlarged mold height 200 mm variety "A" according to technical sales manual (min. mold height remains std., max. mold height increases, platen stroke increases, max. daylight increases, clamp unit will be longer)

Hydraulic:

electrically adjustable variable displacement pump
 with pressure and volume regulation
 Closing movement with position controlled
 proportional valve
 injection with servo valve for injection speed and
 holding pressure
 parallel movement for ejector, corepull,

Pos.	Art.No.	Qty.	Description	Price USD
			injection unit forward during opening, closing	
19	d150043060		N-execution	
20	d150043160		external oil filter station 3-R BU-100	
21	d150070450		ecodrive - innovative speed controlled drive concept with servodrive and operating point optimization (for best overall efficiency through servodrive speed control adjustment and pivoting angle of variable pump). Program ecograph is necessary in addition (according price list). Electric: integrated control cabinet Connection for heating and power not separated	
22	d200003150		interface for conveyor belt execution with switchable socket	
23	d200003300		adapter corepull limit switch Euromap 13 - Amphenol	
24	d209990009		120 vac outlet "Hot" during screw turn with signal located near hopper 120 vac dry contact for color feeder located non-op side injection casting OPT125223 Control:	
25	d250000155		CC200 control package including: - "Windows" style display with 15" TFT-color Touch Screen - Data storage via USB interface - Ethernet network interface - Freely programmable cycle sequence supported by graphical symbols - Screen pages configurable	

Pos.	Art.No.	Qty.	Description	Price USD
			- e-help - Notepad - Alarm Messaging via Email - weekly timer - Micrograph - Microplast - PD-log Screen text english: EN spanish: ES	
26	d250001800		ecograph for energy analysis of IMM	
27	d250003165		Interface for integrated ENGEL robot incl. 1 triggered receptacle for conveyor belt, 3 Phases, 15 AMP	
28	d250003870		interface for potential free contacts (terminal strip) - freely programable (4x digital output, 4x digital input)	
29	d250004010		program optimum motor capacity control during feeding	
30	d250011400		program "virt mould" for viewing and revising of parameter settings and for process opti- mization on PC incl. simulation	
			General: Machine without oil filling (Start-up with zinc containing oil) Machine description english Manual, 2 copies	
31	d300043027		Pneumatic air supply maintenance unit (Filter/Regulator)	
32	d300043031	4	Solenoid operated pneumatic valve 5/2-ways, R1/4" ports, mounted on stationary platen. For airblow only. (1.000,-)	

Pos.	Art.No.	Qty.	Description	Price USD
33	d300043032	4	Solenoid operated pneumatic valve 5/2-ways, R1/4" ports, mounted on moving platen. For airblow only. (1.000,-)	
34	d300043045		machine support pads	
35	d300065490		Painting Standard	
36	d300080000		If the machine will be delivered with robot, it will not be installed onto the machine for pre-acceptance at ENGEL Austria	
37	d390007300		pneumatic shut off nozzle control 4-fold	
38	d400012979		Interface for magnetic quick mold mounting system Euromap 70.0 OPT130149	